

Acetone

SECTION 1 IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

| | | | |
|-----------------------|---|--|----------------|
| Trade name | Acetone | | |
| Synonyms | 2-propanone, Dimethyl ketone, Ketone propane, beta-Ketopropane. | | |
| Use | Industrial use, Intermediate, Paint and Coatings, Personal care, Pesticide, Pharmaceutical, Process/Extraction Solvent, Raw material for chemical processes, Raw material for cosmetic products, Raw material for industry, Raw material for pharmaceuticals, Solvent | | |
| Company | Sasol Chemicals (USA) LLC (an affiliate of Sasol Chemicals North America LLC) | | |
| Address | 900 Threadneedle Ste 100 Houston TX 77079 | | |
| Telephone | CHEMTREC North America Transportation Emergency (24-hr) | | (800) 424-9300 |
| | CHEMTREC World Wide | | (703) 527-3887 |
| | Other Emergencies (24-hr) | | (337) 494-5142 |
| | MSDS and Product Information (8:00am-4:30pm CST) | | (281) 588-3491 |
| | Health and Safety Information (7:30am-4:00pm CST) | | (281) 588-3492 |
| E-mail address | SasolElectronicSDS@us.sasol.com | | |

SECTION 2 HAZARDS IDENTIFICATION

GHS Hazards


| | |
|--|-------------------------------|
| Flammable liquids | Category 2 |
| Eye irritation | Category 2A |
| Specific target organ toxicity - single exposure | Category 3 (Narcotic effects) |

LABEL ELEMENTS**Hazard symbols****Signal word** Danger

Hazard statements H225 Highly flammable liquid and vapour.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.

Precautionary statements

Prevention P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
 P233 Keep container tightly closed.
 P240 Ground/bond container and receiving equipment.



Acetone

- P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P280 Wear protective gloves/ eye protection/ face protection.
P264 Wash skin thoroughly after handling.
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
P271 Use only outdoors or in a well-ventilated area.

Response P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P370 + P378 In case of fire: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide for extinction.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313 If eye irritation persists: Get medical advice/ attention.
P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P312 Call a POISON CENTER or doctor/ physician if you feel unwell.

Storage P403 + P405 + P235 Store locked up in a well-ventilated place. Keep cool.

SECTION 3 COMPOSITION/INFORMATION ON INGREDIENTS

| <u>Components</u> | <u>CAS-No.</u> | <u>Weight percent</u> |
|-------------------|----------------|-----------------------|
| Acetone | 67-64-1 | 99.9 |

See Section 8 for Exposure Guidelines and Section 15 for Regulatory Classifications.


SECTION 4 FIRST AID MEASURES

- Eye contact** Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.
- Skin contact** Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. When symptoms persist or in all cases of doubt seek medical advice. Wash contaminated clothing before re-use.
- Inhalation** Remove to fresh air. If breathing is irregular or stopped, administer artificial respiration. In case of shortness of breath, give oxygen. Call a physician immediately.
- Ingestion** If swallowed, call a poison control centre or doctor immediately. Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person.

SECTION 5 FIREFIGHTING MEASURES

FLAMMABLE PROPERTIES

Fire/explosion Vapours may form explosive mixture with air. Flash back possible over considerable distance. Use water spray to disperse the vapors. NFPA Class IB flammable liquid.



Acetone

| | |
|--|---|
| Suitable extinguishing media | Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide. |
| Protective equipment and precautions for firefighters | In the event of fire, wear self-contained breathing apparatus. |
| Further information | Keep containers and surroundings cool with water spray. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. |

SECTION 6 ACCIDENTAL RELEASE MEASURES

| | |
|--|---|
| Methods and materials for containment and cleaning up | Evacuate personnel to safe areas. Remove all sources of ignition. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Do not flush into surface water or sanitary sewer system. |
|--|---|

SECTION 7 HANDLING AND STORAGE

| | |
|-----------------------------------|--|
| Safe handling advice | Ensure all equipment is electrically grounded before beginning transfer operations. Keep away from heat and sources of ignition. |
| Storage/Transport pressure | Ambient |
| Load/Unload temperature | Ambient |

SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING MEASURES

Air contaminant levels should be controlled below the PEL or TLV for this product (see Exposure Guidelines). Ensure adequate ventilation, especially in confined areas. Use explosion-proof equipment.

PERSONAL PROTECTIVE EQUIPMENT

| | |
|-------------------|---|
| Eyes | Chemical resistant goggles must be worn., Face-shield |
| Skin | Wear suitable protective clothing, gloves and eye/face protection. |
| Inhalation | Respiratory protection is normally not required except in emergencies or when conditions cause excessive airborne levels of mists or vapors. Use NIOSH approved respiratory protection. |

EXPOSURE GUIDELINES

| <u>Components</u> | <u>Exposure limit(s)</u> |
|-------------------|--|
| Acetone | OSHA PEL 1,000 ppm 2,400 mg/m ³ ACGIH TLV (8-hour) 500 ppm ACGIH STEL 750 ppm |

Acetone

PEL= Permissible Exposure Limits
TLV= Threshold Limit Value
EL= Excursion Limit

TWA= Time Weighted Average (8 hr.)
STEL= Short Term Exposure Limit (15 min.)
WEEL= Workplace Environmental Exposure Level

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance liquid;

Colour Clear, colorless

Form liquid

Odour characteristic

Odour Threshold no data available

Flash point -17 °C, 1.4 °F;

Flammability Upper explosion limit: 13.0 %(V)
Lower explosion limit: 2.5 %(V)

Boiling point/boiling range 56 °C, 133 °F;

Melting point/range -95.35 °C, -139.6 °F;

Auto-ignition temperature 465 °C, 869 °F;

Decomposition temperature no data available

Flammability (solid, gas) no data available

Vapour pressure 240 hPa @ 20 °C, 68 °F;

Vapour density no data available

Density 0.79 g/cm³ @ 20 °C, 68 °F;

Specific gravity no data available

Water solubility completely miscible

Viscosity no data available

Viscosity, dynamic 0.32 mPa.s @ 20 °C, 68 °F;

pH no data available

Acetone

| | |
|---|-------------------|
| Evaporation rate | no data available |
| Partition coefficient: n-octanol/water | no data available |
| Volatile organic compounds (VOC) content | 100 % |

SECTION 10 STABILITY AND REACTIVITY

| | |
|---|---|
| Reactivity | Vapours may form explosive mixture with air. |
| Chemical stability | No decomposition if stored and applied as directed. |
| Conditions to avoid | Extremes of temperature and direct sunlight. |
| Hazardous decomposition products | None known. |
| Materials to avoid | Oxidizing agents |
| Hazardous polymerisation | May form explosive peroxides. |

SECTION 11 TOXICOLOGICAL INFORMATION

| | |
|--|---|
| Acute dermal toxicity | LD50 rabbit: > 2,000 mg/kg(literature value) |
| Acute inhalation toxicity | LC50 rat (4 hours): > 20 mg/l (literature value) |
| Acute oral toxicity | LD50 rat: > 2,000 mg/kg (literature value) |
| Skin corrosion/irritation | (rabbit) Moderately irritating, (literature value) |
| Eye damage/irritation | (rabbit) irritating, (literature value) |
| Respiratory or skin sensitization | no data available |
| Germ cell mutagenicity | Genotoxicity in vitro: Type: Ames test System: Salmonella typhimurium; with and without metabolic activation Result: In vitro tests did not show mutagenic effects. (literature value) Genotoxicity in vivo: |

Acetone

no data available

Assessment Mutagenicity:

Based on available data, the classification criteria are not met.

Reproductive toxicity **Reproductive toxicity:**

no data available

Assessment Reproductive toxicity:

no data available

Teratogenicity:

no data available

Assessment teratogenicity:

no data available

STOT - single exposure The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

STOT - repeated exposure no data available

Aspiration toxicity no data available

Carcinogenicity **Assessment carcinogenicity:**
Contains no ingredient listed as a carcinogen

SECTION 12 ECOLOGICAL INFORMATION

Toxicity to fish LC50 (Oncorhynchus mykiss (rainbow trout)) 96 hours: > 100 mg/l; static test (literature value)

Toxicity to aquatic invertebrates EC50 (Daphnia magna (Water flea)) 48 hours: > 100 mg/l; static test (literature value)

Toxicity to algae EC50 (Pseudokirchneriella subcapitata (green algae)) 96 hours: > 100 mg/l; static test (literature value)


Chronic toxicity to aquatic invertebrates NOEC (Daphnia magna (Water flea)) 28 d: > 100 mg/l; flow-through test (literature value)

Biodegradation Readily biodegradable.

OECD Test Guideline 301B (28 d): > 60 % (literature value)

Bioaccumulation no data available

Mobility in soil no data available



Acetone

Other adverse effects no data available

SECTION 13 DISPOSAL CONSIDERATIONS

- Waste Code** F003 (RQ 5,000 Lbs)D001 - Ignitability (RQ 100 LB). Re-evaluation of the product may be required by the user at the time of disposal, since the product uses, transformations, mixtures, contamination, and spillage may change the classification.
- Disposal methods** Dispose of only in accordance with local, state, and federal regulations. Do not contaminate any lakes, streams, ponds, groundwater or soil.
- Empty containers.** Empty containers retain product residue (liquid and/or vapor) and can be dangerous. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION; THEY MAY EXPLODE AND CAUSE INJURY OR DEATH. Empty drums should be completely drained, triple-rinsed, properly bunged and promptly returned to a drum reconditioner, or properly disposed.

SECTION 14 TRANSPORT INFORMATION

- DOT** UN 1090, Acetone, 3, II
When shipped in quantities greater than 5,000 lbs, RQ must be added to the shipping description.
- IATA** UN 1090, Acetone, 3, II
When shipped in quantities greater than 5,000 lbs, RQ must be added to the shipping description.
- IMDG** UN 1090, Acetone, 3, II
When shipped in quantities greater than 5,000 lbs, RQ must be added to the shipping description.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Remarks no data available

SECTION 15 REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS

OSHA Hazards (HCS 1994)

Flammable liquid, Eye irritant

TSCA Inventory Listing

Components
Acetone

CAS-No.
67-64-1

SARA 302 Status
Components

CAS-No.

Weight percent

Acetone

SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 311/312 Classification

"Fire hazard", "Immediate (acute) health hazard"

SARA 313 Chemical

Components

CAS-No.

Weight percent

SARA 313: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

US. EPA CERCLA Hazardous Substances (40 CFR 302)

Components

Reportable Quantity

Weight percent

Acetone

5,000 LB

99.9 %

INTERNATIONAL REGULATIONS

WHMIS Classification

Class B, Division 2: Flammable liquid.

Class D, Division 2, Subdivision B: Toxic material.

European Union


Classification according to Regulation (EU) 1272/2008.

Flammable liquids, Category 2

Eye irritation, Category 2

Specific target organ toxicity - single exposure, Category 3 (Narcotic effects)

| | |
|---|------------|
| Australia. Inventory of Chemical Substances (AICS) | Listed |
| Japan. Inventory of Existing and New Chemical Substances (ENCS) | Listed |
| Japan. Industrial Safety & Health Law (ISHL) Inventory | Listed |
| Canada. Domestic Substances List (DSL) Inventory | Listed |
| Canadian Non-Domestic Substance Listing (NDSL) | Not listed |
| European Inventory of Existing Commercial Chemical Substances (EINECS) Listing | Listed |
| Philippines. Inventory of Chemicals / Chemical Substances (PICCS) | Listed |
| Korea. Existing Chemicals Inventory (KECI) | Listed |
| China. Inventory of Existing Chemical Substances (IECSC) | Listed |
| Mexico. National Inventory of Chemical Substances (INSQ) | Listed |
| New Zealand. Inventory of Chemicals (NZIoC) | Listed |
| Switzerland. Inventory of Notified New Substances (CHINV) | Listed |
| Taiwan. National Existing Chemical Inventory (NECI) | Listed |



Acetone

Please note: The names and CAS numbers which are used for this product in the stated inventories may deviate from the information which is listed in Section 3.

STATE REGULATIONS

California Prop. 65

Components

none

CAS-No.

SECTION 16 OTHER INFORMATION

HAZARD RATINGS

| | <u>Health</u> | <u>Flammability</u> | <u>Physical Hazard/ Instability</u> |
|--------------|---------------|---------------------|---|
| HMIS® | 2 | 3 | 0 |
| NFPA | 2 | 3 | 0 |

THE DATA AND INFORMATION CONTAINED HEREIN ARE BEING FURNISHED FOR INFORMATIONAL PURPOSES ONLY, UPON THE EXPRESS CONDITION THAT EACH CUSTOMER SHALL MAKE ITS OWN ASSESSMENT OF APPROPRIATE USE AND APPROPRIATE SHIPPING, TRANSFER AND STORAGE MATERIALS AND PROCEDURES FOR SASOL CHEMICALS (USA) LLC'S PRODUCTS. ALTHOUGH BASED ON INFORMATION SOURCES WHICH SASOL CHEMICALS (USA) LLC CONSIDERS ACCURATE AND RELIABLE, SASOL CHEMICALS (USA) LLC MAKES NO WARRANTY, EITHER EXPRESS OR IMPLIED, INCLUDING ANY WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, REGARDING THE VALIDITY OF THIS INFORMATION, THE INFORMATION SOURCES UPON WHICH THE SAME ARE BASED, OR THE RESULTS TO BE OBTAINED, AND EXPRESSLY DISCLAIMS LIABILITIES FOR DAMAGES OR INJURIES RESULTING FROM THE USE THEREOF.
