PRI	MATERI	MATERIAL SAFETY DATA SHEET		N/A=Not Applicable	
Prepared by: Regulatory Affairs Dept.	(Prepared	According to 29 CFF	R 1910.1200)	Effective Da	te: 1/09 Revision: n/a
SECTION 1-F	PRODUCT IDENTIFI	CATION AND S	UPPLIER INFORM	IATION	_
Manufacturer's Name:	Product Name: Prin	Product Name: Prime Time		Supplier's Name:	
Misco Products Corporation	Generic Name: Wa	terbased Urethane W	ood Finish		
Manufacturer's Address:	Chemical Family: U	Chemical Family: Urethane Dispersion		Supplier's Address:	
1048 Stinson Drive Reading, PA 19605	Formula: Proprietar	ry			
Manufacturer's Phone #: (610) 926-4106			Supplier	's Phone #:	
	SECTION 2-ING	REDIENT INFOR	RMATION		
CHEMICAL NAME	CAS NO.	WT. %	PEL	TWA-TLV	STEL-TLV
Water	7732-18-5	to 100			
Oil Modified Urethane Dispersion	N/A	25 to 30			
N-Methyl Pyrrolidone	872-50-4	0 to 5	100 ppm	100 ppm	
Polyether Modified Dimethylpolysiloxane	N/A	> 0.1			
SECTION 3-PHYSICA	I DATA	SI	ECTION 4-FIRE AN	ND EXPLOSION I	HAZARD DATA

SECTION 3-PHYSICAL DATA		SECTION 4-FIRE AND EXPLOSION HAZARD DATA		
Boiling Point (°F): 212 F.	Specific Gravity: 1.01	Flash Point (Method Used): N/A		
Vapor Pressure: 20mm Hg @ 68 F.	Vapor Density (Air=1): >1	Upper Explosion Limit: N/A	Lower Explosion Limit: N/A	
% Volatile: 65+	pH: 7.5-8.0	Extinguishing Media: N/A		
Solubility in Water: Dispersible	Evaporation Rate (Water=1): <1	Special Firefighting Procedures: Non F	lammable	
Physical Description: Moderately viscous milky liquid with characteristic odor.		Unusual Fire and Explosion Hazards: N/A		
VOC Content (Subpart D §59.406): 180 g/l				

SECTION 5-REACTIVITY DATA Stability: Stable Hazardous Polymerization: May occur through oxidation, leading to exothermic

reaction. Heat generated by oxidation may lead to spontaneous combustion of materials such as rags, paper towels, etc., used for clean-up. Hazards Decomposition Products: Will not occur. Incompatibility (Materials to Avoid): None

SECTION 6-STORAGE AND HANDLING INFORMATION

Keep out of reach of children. For use by trained personnel only. Keep unauthorized personnel away when applying to floor. Keep container closed during storage. For institutional and industrial use only. Avoid contact with eyes, skin and clothing. Wear rubber gloves when handling. Wear protective rubber boots when applying to floor. Avoid breathing of vapors. Use in well-ventilated areas at all times.

SECTION 7-HEALTH HAZARDS AND FIRST AID

Effects of Overexposure:

Skin: Prolonged or repeated contact may cause dermatitis.

Eyes: Eye irritant. May cause redness or swelling.

Inhalation: Prolonged breathing of vapors may cause dizziness, nausea, and headaches.

Ingestion: May be irritating to the mouth, throat, and gastrointestinal system. Vomiting and diarrhea expected with large doses.

First Aid Procedures:

Skin: Flush with water, then wash with mild soap and water. Seek medical attention if irritation persists.

Eyes: Flush with large quantities of water, holding eyelids open. Seek medical attention immediately.

Inhalation: Remove victim to fresh air. Seek medical attention if symptoms persist. Ingestion: Dilute with 2 glasses of water. Seek medical attention immediately.

SECTION 8-SPECIAL PROTECTION INFORMATION

Respiratory Protection: Use in well-ventilated area. Organic vapor respirator when using in poorly ventilated areas.

Ventilation Requirements: Provide local exhaust to keep TLV of Section 2 ingredients below acceptable limit. Open doors and windows during use. Continue to ventilate during drying period.

Protective Gloves: Rubber or chemical resistant gloves should be worn.

Eye Protection: Splash goggles should be worn when handling.

Other Protective Equipment: Eye wash station should be made available nearby. Chemical resistant footwear (rubber boots) when using product on floor.

SECTION 9-SPILL OR LEAK PROCEDURES

Steps to be taken in Case Material is Released or Spilled: Floors will become slippery Avoid walking in product. Keep unessential personnel away. Mop up or otherwise absorb and hold disposal. Avoid discharge to sewer or open waterways.

Waste Disposal Method: Any method in accordance with local, state and federal laws. Best method is to recycle or reuse for intended purpose. Consult local authorities for disposal in public sewer. Materials used to absorb product should be soaked in water-filled containers or rinsed with water prior to discarding in trash receptacles. Do not dispose of into storm drain, stream, river or to ground. Rinse container thoroughly before discarding in trash

SECTION 10-REGULATORY INFORMATION

SARA Title III - Section 311/312 -Hazard Categories:	Shipping Information:	HMIS Hazardous Materials
No - Fire Hazard	FOR CONTAINERS > 1 Gallon: Floor Wax	Identification System
No - Sudden Release of Pressure Hazard		Health 2
No - Reactivity Hazard	FOR 1 GALLON CONTAINERS: Floor Wax	Flammability 0
Yes - Immediate (acute) Health Hazard		Reactivity 0
No - Delayed (chronic) Health Hazard	FOR CONTAINERS < 1 GALLON: Floor Wax	Personal Protection B

FOR EMERGENCY MEDICAL OR TRANSPORT INFORMATION: CHEM-TEL, Inc. @ 800-255-3924 (24 hours, 7 days per week)

This product contains the following toxic chemical(s) subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and of 40 CFR 372.

CAS# **Chemical Name** Percent by Weight None

This product contains the following chemical(s) which have been established to be either a carcinogen or suspected carcinogen.

CAS# **Chemical Name** Percent by Weight

None

SECTION 11-OTHER INFORMATION

This company cannot anticipate all conditions of handling and use of this product. Therefore, this company accepts no responsibility for results obtained by the application of this information, or the safety and suitability of our products either alone or in combination with other products. It is the responsibility of the user to provide a safe workplace, using the health and safety information contained herein as a guide. This company will accept no liability for damages or loss incurred from the improper handling and use of this product.